



Configuration Tool

User Manual

(RTX200A/B, RTMU86, RT820, RT840)



Contents

General Introduction.....	4
Introduction.....	4
Supported devices	4
Start to Use	4
Configuration User Guide	5
1. Main interface	5
1) Configuration methods.....	5
2) Language switch	5
3) Switch interface	6
2. Online device configuration	6
1) Device info	6
2) Device configuration	6
3. Offline device	6
4. Configuration interface	7
1) Work mode	7
2) Scan set.....	9
3) Advanced settings	11
4) NFC Card Reading Set: “Swipe”	13
5) Network settings	15
6) Generate the configuration QR code	18
7) Save configuration	19
8) Reset the default password.....	19
5. Quick configuration QR code	20
1) USB mode.....	20
2) 232 mode	21
3) TTL mode.....	22

4) 485 mode	23
5) Wiegand mode	24
A. Wiegand 26	24
B. Wiegand 34	25
C. Scanning QR code output format.....	26
6. Universal configuration QR code.	29
A. Add barcode function.....	29
B. Add enter function	30
C. Add linefeed function	30
D. Open read card function	31
E. Change swipe card output format.....	31
F. Swipe card positive sequence output.....	33
G. Swipe card inverted sequence output	34
H. Swipe card output length	35
I. Set single mode.....	35
J. Set interval mode	36
K. Set scanning code light feedback.....	37
L. Set baud rate	38
M. Level change.....	39
N. Restart the device	40
Explanation of the Output Format	41
Wiegand output format comparison	41
FAQ.....	44

General Introduction

Introduction

This software is used for RTX200A/B, RTMU86, RT820, RT840. Its main functions include:

- ✧ Online device: get the device info and the parameters of the settings, can also modify the settings and interacting with device
- ✧ Connect or save the device configuration settings
- ✧ Generate configuration QR code
- ✧ Language switch


Supported devices

RTX200A/B, RTMU86, RT820, RTX200, RT840

Note: When you run this ConfigTool, it's highly recommended to modify the PC's resolution to: 1280*768, so as to show the interface fully.


Start to Use

The software do not need to install, after decompressing the file, double click the ConfigTool.exe icon to run it. Click the language switch (red circle below) and come to the English interface



Configuration User Guide

1. Main interface



1) Configuration methods

The tool support both online and offline mode.

Offline device: (all the device will need offline config if the device was not USB connection) you can select the corresponding model and choose the settings you want, then generate configuration QR code, and scan it to achieve the configuration.

Online device: (**only support USB connection**), the device connects to PC, click connect to connect the scanner with this tool, it will detect the device and get its settings.

2) Language switch

The Config tool support both Chinese and English, click “中” or “EN”

3) Switch interface

If already entered the other interface, click “main “to back to the main interface or click “return”. You can also switch the configuration interface via Tab

2. Online device configuration

1) Device info

The ConfigTool can detect the device which connected to PC(**Only for USB connection**), click connect device, after success, it will shows the device connection status and its firmware version.

When the device was connected to computer, click connect the tool will connect with the device successfully.

Notes: if the work mode was develop-USB keyboard-protocol, you will need to configure by scanning the configuration QR code which was generated by the tool. This mode cannot connect the tool.

2) Device configuration

After the device was connected successfully, click “next” in the main interface, then you will see the pic below and you can choose all of setting as your needs, and then click next to enter the detail pages.

The screenshot shows a configuration window with the following elements:

- Set Password:** A text input field containing the password "34567887654321". To the right are two buttons: "→ Next" and "→ Main".
- Work mode:** Two radio button options: "Ordinary" (selected) and "Develop".
- Output:** Three radio button options: "RS485/232", "Wigan" (selected), and "Ethernet".
- Development mode:** Two radio button options: "Protocol" (selected) and "485 one more".
- Wiegand format:** Two radio button options: "Wigan34" and "Wigan2€" (selected).

3. Offline device

You can also offline use the configTool, run it and select the corresponding device, and then click next to configure the options you want and then generate setting codes.

4. Configuration interface

Set Password: [→ Next](#) [→ Main](#)

Work mode

Ordinary Develop

Output

Keyboard RS485/232 TTL WIFI

WIFI/Ethernet/2G output set

TCP TCP protocol HTTP/HTTPS HTTP protocol/HTTPS protocol

1) Work mode

- Working mode: ordinary, develop

When need to write a program to control the scanner or calling the scanner output interface, need to use develop mode, the others cases use ordinary mode.

- Output interface: select the corresponding output interface according to the device you purchase. One device can only support one output interface.
- Development mode

The development mode means the way you choose when doing develop, all the devices select “protocol “at present.

Set Password: [→ Next](#) [→ Main](#)

Work mode

Ordinary Develop

Output

Keyboard RS485/232 TTL WIFI

Development mode

Protocol 485 one more

➤ Serial parameter

When the output interface selected RS232/RS485/TTL, need to set up the corresponding serial parameters, such as baud rate, stop bit, check bit, etc.

➤ WIFI/Ethernet/2G output interface settings

When the output interface selected WIFI/Ethernet/2G, need to select corresponding networking protocol.

The difference between TCP and TCP protocol, HTTP and HTTP protocol: TCP/HTTP pass through the content of the QR code, while TCP protocol/HTTP protocol upload character string which has filed format. For more details, please check “ QR code scanner WIFI interface specification V1.2”

The screenshot shows a configuration page with a password field containing '34567887654321'. At the top right are buttons for 'Next' and 'Main'. The 'Work mode' section has 'Develop' selected. The 'Output' section has 'WIFI' selected. The 'Development mode' section has 'Protocol' selected. The 'WIFI/Ethernet/2G output set' section has 'HTTP/HTTPS' selected.

➤ Wiegand output format

If selected Wiegand output, need to specify whether to choose Wiegand 26 protocol or Wiegand 34 protocol, this two protocol can be switch.

The screenshot shows the same configuration page as above, but with 'Ordinary' selected in the 'Work mode' section. In the 'Output' section, 'Wigan' is selected. In the 'Wiegand format' section, 'Wigan26' is selected.

2) Scan set

➤ Symbolologies

Select the “code” firstly, and then select the code you need to read in the optional bar

The screenshot shows the 'Scan set' configuration screen. At the top, there is a 'Set Password:' field with the value '34567887654321'. To the right are navigation buttons: 'Return' and 'Main'. Below the password field are four tabs: 'Scan set', 'Advanced', 'Swipe', and 'Net'. The 'Scan set' tab is active. On the left, there is a list of options: 'Code' (checked), 'Prefix suffix', 'EnterWrap', 'Scan Mode', 'Action', and 'Backlight'. The 'Code' option is selected, and a sub-menu is displayed in the center. This sub-menu is titled 'Code' and contains a list of code types: 'QR' (checked), 'PDF417', 'CODE128', 'ISBN10', 'ISBN13', 'CODE39', 'CODE93', 'EAN13', and 'ITF'. To the right of the sub-menu are buttons: 'Config code', 'Save', 'Reset Password', and 'Exit'. Below these buttons is the text 'QR Code Position'.

➤ Prefix and suffix

Select “prefix suffix” first, and then fill in the prefix or suffix content which need to set. The prefix and suffix format setting is supported.

The screenshot shows the 'Scan set' configuration screen. At the top, there is a 'Set Password:' field with the value '34567887654321'. To the right are navigation buttons: 'Return' and 'Main'. Below the password field are four tabs: 'Scan set', 'Advanced', 'Swipe', and 'Net'. The 'Scan set' tab is active. On the left, there is a list of options: 'Code' (checked), 'Prefix suffix' (checked), 'EnterWrap', 'Scan Mode', 'Action', and 'Backlight'. The 'Prefix suffix' option is selected, and a sub-menu is displayed in the center. This sub-menu is titled 'PrefixSuffix' and contains a 'Format' section with two radio buttons: 'char' (selected) and 'hex'. Below the format section are two input fields: 'Scan Prefix:' and 'Scan Suffix:'. To the right of the sub-menu are buttons: 'Config code', 'Save', 'Reset Password', and 'Exit'. Below these buttons is the text 'QR Code Position'.

➤ “Enter wrap”

First select “Enter wrap” and then select enter or line feed.


➤ Backlight

Backlight means the white light fill light in the scanner

➤ The scan mode


Single mode means that the same code cannot be scanned twice continuously, for example, if scanned code A one time, then we can't scan this same code again. But, if scan code A one-time then scan code B one time, after this it can scan code A again.

Interval mode means the interval time between the two scans of the same code. The unit is ms, if need 1 second interval, then fill in 1000.




➤ Scan action

The "action" means the device feedback after the device scanned the code. According to the function that the device supported, it can be beep, or flash light of different color. The delay means the length of the action, default is okay for most cases.



➤ Brightness control


Brightness used to control the background light brightness of the scanner



3) Advanced settings

➤ Device number

The device number can be set, the device number can be obtained via the protocol instruction, or in the Ethernet/WIFI output can be uploaded to the server together with the QR code contents. **The content of the device number can only be Int data.**



➤ Change the configuration password

The configuration password can be changed in case of someone tamper it, please keep the new password in mind, will need to fill in the new password first then start config when next configuration is needed.

The screenshot shows a web-based configuration interface. At the top, there is a 'Set Password:' field containing the value '34567887654321'. To the right of this field are two buttons: '→ Return' and '→ Main'. Below the password field are four tabs: 'Scan set', 'Advanced', 'Swipe', and 'Net'. The 'Advanced' tab is selected. On the left side of the 'Advanced' tab, there are three checked checkboxes: 'Device num', 'ChangePasswo', and 'Output format'. The 'ChangePasswo' checkbox is highlighted with a red box. A dialog box titled 'ChangePassword' is open in the center, containing a 'ChangePassword' label, a 'New password:' input field, and a 'Confirm password:' input field. To the right of the dialog box are four buttons: 'Config code', 'Save', 'Reset Password', and 'Exit'. Below these buttons is the text 'QR Code Position'.

➤ Output format

This option are [only for RTMU86's wiegand interface](#). For others devices, please select "direct" output, otherwise there would be no data output when scan code.


For RTMU86's wiegand interface, please select others output format except the "direct", select according to the controller you are using. You can also refer the configuration code below.

The screenshot shows the same web-based configuration interface as above. The 'Advanced' tab is still selected. The 'Output format' checkbox is now checked and highlighted with a red box. A dialog box titled 'Output format' is open in the center, containing a list of radio button options: 'Direct', 'Digital Char turn Hex', 'Digital Char turn Hex reverse', 'Hex Char turn Hex', 'Hex Char turn hex Reverse', 'Decimal turn PIDVID', and 'Decimal turn PIDVID reverse'. The 'Direct' option is selected. To the right of the dialog box are the same four buttons: 'Config code', 'Save', 'Reset Password', and 'Exit'. Below these buttons is the text 'QR Code Position'.

4) NFC Card Reading Set: "Swipe"


➤ Read NFC switch

If need to read NFC cards, then select Swipe> Switch, then select Open for "NFC switch".




➤ Output set

The card output set can be set, if the device was wiegand output, mostly select "direct", for other output methods select as your needs. The "start output bit"are only valid for Chinese ID card.




➤ Prefix and suffix

This function can be use for adding prefix and suffix for card number.




➤ **Swipe action**

Swipe action means the action when read NFC cards.



➤ **Sequence**


Support the card number output in positive order or reverse order.



5) Network settings

➤ WIFI setting


This option are used to configure the WiFi account and password that the device are going to connect.



➤ Transmission success/ failed action


Transmission success/failed: it means the action that the data was sent successfully via internet

If set TCP protocol mode or HTTP protocol mode, after the server received data, it will return "code=0000" first, then will show the success action, error value or didn't return will show fail action



➤ TCP/UDPara parameter

Set the TCP server address, port number, and time-out period. (within 5 seconds)




➤ HTTP parameter

Set the HTTP server address, format: <http://serveraddr:port/path>.




➤ Heartbeat setting

The heartbeat can be set under TCP mode, the http mode was not supported



➤ IP mode


Support dynamic IP and static IP configuration, for static IP, need to fill in the IP address, sub-off mask, gateway. Dynamic IP not needed.



6) Generate the configuration QR code

After configured all the above options, click “config code”, a configuration QR code will be shows in the right side. Then use the scanner to scan it, after beep sound or light feedback, it means configuration success. Now power off and restart the scanner so that the configuration will become valid.

The above options do not need to select all, just configure as your needs.




7) Save configuration

For the online use mode, click 'save' to save the configuration to the scanner directly and no need to scan the setting code. Then power off and re-plug the scanner so the new configuration will become valid.



8) Reset the default password

If you changed the password but forgot it, then you can use online configure, after connect to the tool, click "reset password" the password will become the default password(1234567887654321)



5. Quick configuration QR code

Using methods: Use the scanner to scan the configuration QR code you need, then re-plug the scanner, configuration success.

1) USB mode



USB-ordinary mode



USB-develop mode-protocol



USB-develop mode-USBHID

2) 232 mode



RS232-ordinary mode-115200



RS232-develop mode-115200

3) TTL mode



TTL- ordinary mode- 115200



TTL- develop mode-115200

4) 485 mode



485- Ordinary mode-115200



486- Develop mode-115200

5) Wiegand mode

Using method: this configuration was comprised of 3 parts: Wiegand protocol (26 or 34) and Wiegand level(3.3v or 4.4v) and scan code/read card output format(the output format can refer to the universal configuration QR code). The device can scan the wiegand26 or Wiegand 34 configuration QR code, if there is still no uploaded data in background, scan the configuration code which change the scanning output format. If doesn't know use which one, could try all of them. (the scanner will need to restart after each configuration)

A. Wiegand 26



Wiegand26-PIDVID inverted sequence-3.3V



Wiegand26-PIDVID inverted sequence-4.3V

B. Wiegand 34



Wiegand34- number to HEX- 3.3V



Wiegand34- number to hex-4.3v

C. Scanning QR code output format



Numeric character to hex



Numeric character to hex inverted sequence



Hexadecimal to HEX



Hexadecimal to hex inverted sequence



Decimal to PIDVID



Decimal to PIDVID inverted sequence

6. Universal configuration QR code.

A. Add barcode function



Add scan barcode function

B. Add enter function



Add enter

C. Add linefeed function



Add linefeed

D. Open read card function



Open read card function

E. Change swipe card output format



swipe card decimal output



Swipe card hexadecimal output



Swipe card output directly

F. Swipe card positive sequence output



General cards positive sequence



ID card positive sequence(Chinese ID card only)

G. Swipe card inverted sequence output



General cards inverted sequence



ID card inverted sequence (Chinese ID card only)

H. Swipe card output length

(for Chinese ID card only)



I. Set single mode



Single mode

J. Set interval mode



1 second time interval



2 second time interval



3 second time interval

K. Set scanning code light feedback



Add lighting feedback function

L. Set baud rate



M. Level change



3.3V



4.3V

N. Restart the device



Device restart

Explanation of the Output Format

Main interface -> Advanced -> Output format:

Ex: read the barcode: 12345678

1. Direct
Output the scanned original data.
The output is: 38 37 36 35 34 33 32 31
2. Digital Char turn Hex
Convert string to Integer
"12345678" is converted to 12345678 (HEX 00 BC 61 4E)
3. Digital Char turn Hex reverse
Convert string to int, and then int high low
"12345678" is converted to 1315027968 (HEX 4E 61 BC 00)
"12345678" is converted to 5136828 (HEX 4E 61 BC)
4. Hex Char turn Hex
Convert Hex string to Hex
"12345678" is converted to 2018915346 (HEX 78 56 34 12)
5. Hex Char turn Hex Reverse
Convert Hex string to Hex
"12345678" is converted to 305419896 (HEX 12 34 56 78)
6. Decimal turn PIDVID format output
7. Decimal turn PIDVID format output reverse

Wiegand output format comparison

		Wigan 26
--	--	----------

Card Type	Card No.	Direct	Convert to decimal output	Convert to Hex output
NTAG213	046D61EAD45B81	13917057(D45B81)	"13917057" (3133393137303537)	"D45B81" (44 34 35 42 38 31)
MF1S50	A2DABD8D	14335373(DABD8D)	"14335373"	"DABD8D"
FM11RF08	BD7B88E3	8095971(7B88E3)	"8095971"	"7B88E3"

Wigan 34

Card Type	Card No.	Direct	Convert to decimal output	Convert to Hex output
NTAG213	046D61EAD45B81	3937785601(EAD45B81)	"3937785601" (33393337373835363031)	"EAD45B81" (4541443435423831)
MF1S50	A2DABD8D	2732244365(A2DABD8D)	"2732244365"	"A2DABD8D"
FM11RF08	BD7B88E3	3178989795(BD7B88E3)	"3178989795"	"BD7B88E3"

Remark:

Direct: output the original data directly.

For example, if the Card No. is 01 02 03, directly output three bytes of data and display the Card No. as 66051

Convert to decimal output: convert Hex data to decimal and then to decimal string.

For example, if you want to convert the 0x81 at the end of the Card No. to "129", it will actually be displayed as 0x393231, and then converted to a decimal number 3748401

Convert to Hex output: convert Hex data to Hex string.

For example, if you want to convert the card number 0x046D to "046D", the actual display is 0x64363430 and then converted to decimal number 1681273904

Once set to decimal or Hex output, the outputted Card No. is the ASCII value of the converted string

1) in the configuration tool, it shows connect failed when click connect device.

(1) only the USB device can connect to the configuration tool, while the others need to scan the configuration code to config, which means generate the configuration QR code then use the scanner to scan.

(2) when the USB device was configured into develop mode, it may cannot connect to the tool, can scan the configuration QR code to configure the scanner to ordinary mode then connect to the tool

(3) Maybe the USB port of the computer was occupied by other programs. You could scan the configuration QR code to config.

2) when scanning configuration QR code, there is no response

(1) If changed password, then use the changed password to generate the configuration QR code.

If the changed password was lost, connect the config tool then click “reset password”, after this you could use the default password “1234567887654321”to configure. If cannot connected to the tool, please contact customer service.

(2) Please check whether the format of the configuration was correct, for example: if the HTTP server address added port number, if the prefix and the suffix format which was selected and filled in the tool was correct, whether the device number was “Int” data.

(3) The configuration QR code which was generated by the tool, it’s better to send a screenshot to mobile phone rather than take a photo then use the scanner to scan.

3) When scanning barcodes there is no response.

Whether the device was configured the scanning barcodes function, if not, you could configure it in the tool. If still cannot scan after configuration, please contact customer service.

4) After the device was configured, there is no output content.

The different output interface has different testing methods. For the USB device, you could see the output content in a TXT or Word file, for the serial device (RS232, TTL etc.), you will need to see the output content in

a serial debugging tool, for the Wiegand device, need to see the output content in the Wiegand controller background, and for the Ethernet and Wi-Fi device, you will need to build server first then receive data.

5) After scanning there is error code or messy code.

In the develop mode, the data upload by the scanner was according to the communication protocol, including command header, command word etc., you could refer to the communication protocol to proceed the data parsing.